



# SERIES 212 | Composite Valves

Composite, Engineered Plastic Valves

## Applications

Water purification and conditioning in commercial/industrial markets, with membrane based reverse osmosis systems. Reverse osmosis systems are found in several drinking water applications from restaurant, food and beverage equipment to grocery store produce misting.



## Features & Benefits

### • Tested and certified by NSF international:

- NSF 61 Annex G: Drinking Water System Components
- NSF 169: Special Purpose Food Equipment and Devices
- NSF 42: Drinking Water Treatment Units – Material and Structural Integrity Requirements
- NSF 372: Drinking Water System Components – Lead Content Certification

### • Modular design with FasN™ technology, the world's first universal connection system

- The new ASCO FasN technology enables a quick and reliable connection system
- Available in Turn & Lock, NPT Thread, and Solvent Bond

### • Up to 150 psi and 180°F

- ASCO provides the most reliable valve on the market, with the highest performance

### • Increased reliability


- ASCO's innovative design is tested for over 1 million cycles

### • Low power coils: 6.3 W in AC and 6.9 W in DC normally closed versions

## FasN Connection System

Reliable and secure connections

- Easy to install
- Save time when replacing a valve
- Ability to mix the types of connections on a single valve
- Fit with Copper (CTS), PEX or PVC pipe



## Specifications

Pipe/Tubing Type	FasN End Connection	MOPD (Water)	Fluid Temperature	Operation	Port Size	Wattage
NPT Thread	NPT Threaded Pipe	150 psi (10.3 bar)	180°F (82°C)	Normally Closed	1/2"	AC = 6.3W
Copper (CTS), PEX Tubing	Turn & Lock				3/4"	DC = 6.9W
PVC* Pipe	Solvent Bond	150 psi (10.3 bar)	180°F (82°C)	Normally Open**	1/2"	AC = 11W
					3/4"	DC = 10W

\*For PVC tubing, limitation on Fluid temperature is 73°F/23°C for NSF -61, 122°F/50°C for NSF 372

\*\* For NO version with DC coils, maximum MOPD on water is 90 PSI, with AC Coil is 120 psi

